

IMPACT TH-170 SERIES

Portable Dynamic Hardness Tester





TH-170
IMPACT DEVICE D



TH-172
IMPACT DEVICE C



TH-174
IMPACT DEVICE DL

FEATURES

The world famous IMPACT™ series, part of the unbeatable series of TIME dynamic Leeb hardness testers offer very affordable, but accurate hardness testing solution for on-site testing in workshops and in field operation. The units assure accurate and reliable measurement. All results and statistics can be directly printed to the optional compact fast thermal printer. Any metallic products with a minimum solid mass starting from 0.5kg can be tested according to the Leeb principle. The display shows hardness values in all common scales, such as HRC, HRB, HV, HB, HS, and HLD.

The instrument is equipped with replaceable batteries providing 16 hours continuous operation.

- Dynamic rapid hardness test procedure
- TH-170 Impact device D integrated
- TH-172 Impact device C applying low impact energy for surface hardened components and thin walled components
- TH-174 Impact device DL for testing in confined spaces
- Wide measuring range
- Direct display of hardness Rockwell HRB, HRC, Vickers HV, Brinell HB, Shore HS, Leeb HL
- For most metallic materials
- Automatic gravity compensation for testing at any angle
- Simple handling and low test expenditure
- High accuracy $\pm 0.5\%$
- Clear LCD display showing all functions and parameters
- Conforms to ASTM A 956 and DIN 50156

TECHNICAL SPECIFICATIONS

Hardness parameter	HRC, HRB, HV, HB, HS, HL
Accuracy	Within ± 6 HLD (TH-170) Within ± 12 HLC (TH-172) Within ± 12 HLDL (TH-174)
Statistics	Average (max. 270 in 9 groups)
Output	USB
Min. Surface roughness of workpiece	1.6 μ m (Ra) (TH-170/174), 0.4 μ m (Ra) (TH-172)
Impact device integrated	D (TH-170) C (TH-172) DL (TH-174)
Needle front section of DL-device (TH-174)	Diameter = 4.2mm Length = 50mm
Max. hardness value	940HV (TH-170) 1000HV (TH-172) 950HV (TH-174)
Workpiece radius (convex/concave)	Rmin = 50mm (with support ring Rmin= 10mm)
Workpiece minimum weight	2kg - 5kg on solid support (TH-170/174) 0.05kg - 2kg with coupling paste 0.5 - 1.5kg on solid support (TH-172) 0.02 - 0.5kg with coupling paste
Workpiece min. thickness coupled	5mm (TH-170/174); 1mm (TH-172)
Workpiece min. case hardened depth	0.8mm (TH-170/174), 0.2mm (TH-172)
Indentation depth	See page: Impact devices data
Continuous working time	150 h (without backlight)
Power	Batteries AAA (2 pcs)
Operating temperature	0°C to 40°C
Overall dimensions	155mm x 24mm x 55mm (TH-170/172) 210mm x 24mm x 55mm (TH-174)
Weight	180gr (TH-170/172) or 200gr (TH-174)

STANDARD DELIVERY

- Instrument with integrated impact device type D, C or DL
- Hardness test block with HLD-, HLC- or HLDL-value
- AAA Batteries (2pcs)
- Cleaning brush
- Coupling paste
- Support ring small
- USB communication cable
- USB driver cd
- INNOVATEST® certificate
- Manual
- Carrying case

OPTIONAL ACCESSORIES

- UKAS Reference hardness blocks
- Support rings for convex, concave and spherical surfaces (only TH-170/172) (see page 93)

ORDER DETAILS

- TH-170** Dynamic hardness tester with integrated impact device D
TH-172 Dynamic hardness tester with integrated impact device C
TH-174 Dynamic hardness tester with integrated impact device DL

SUPPORT RINGS



HARDNESS TEST BLOCK



Represented by:

CORPORATE HEAD OFFICE

MANUFACTURING, DISTRIBUTION & SERVICE

INNOVATEST Europe BV

Borgharenweg 140
6222 AA Maastricht (The Netherlands)
Phone: +31 43 3520060
Fax: +31 43 3631168
Email: info@innovatest-europe.com

INNOVATEST Benelux BVBA

SALES & SERVICE

Phone: +32 12 779002
Fax: +32 12 779003
E-mail: info@innovatest-benelux.com

INNOVATEST Shanghai Co., Ltd.

DISTRIBUTION, SALES & SERVICE

101, Bld. 7, No. 59 Shennan Road,
Minhang District, Shanghai, P.R. China
Zip code: 201108
Phone: +86 21 34635955
Fax: +86 21 34635269
E-mail: info@innovatest-shanghai.com

Changes in products and/or product specifications can emerge due to new technologies and continuous development. We reserve the right to change or modify specifications of products without prior notice. We recommend you to contact our sales office for up-to-date information.

© All rights reserved

www.innovatest-europe.com