

Sylvac S_Dial ONE Digital Indicator

The tough but accurate new S_Dial ONE indicators from Sylvac are available with measuring capacities of 12.5mm and 25mm and have an impressive repeatability specification of 0.002mm. Designed to operate within harsh measuring environments, such as in close proximity to machine tools, the S_Dial ONE boasts an IP67 rating, according to IEC 60529, rendering it resistant to the ingress of water and coolant even when fitted with a data connection cable. Manufactured from materials that are able to withstand extended shop floor use, the new S_Dial ONE can be fitted with a wide range of contact points.



Features

- Integrated, ergonomic lifting device (can be removed)
- Large LCD digital readout
- Direct metric/inch conversion
- Preset
- Zero setting
- Extended battery life of 3,300 hours
- Selection of measuring direction
- Programmable by PC
- Direct RS232, USB, Digimatic output
- Lithium CR2302 battery included



SYLVAC S_DIAL ONE DIGITAL INDICATOR

Code No	Range	Resolution	Price (£)
30-905-0121	12.5mm / 0.5"	0.01mm / 0.0005"	£226.00 Q
30-905-0131	12.5mm / 0.5"	0.001mm / 0.00005"	£280.00 Q
30-905-0141	25mm / 1.0"	0.01mm / 0.0005"	£244.00 Q
30-905-0151	25mm / 1.0"	0.001mm / 0.00005"	£300.00 Q

CABLE

Code No	Description	Price (£)
30-926-6721	Proximity data cable USB	£70.00 I

See page 251 for data transmission options